

New Customer
 Existing Customer

Do we have your Secures Sales Agreement on file?
 Yes No

Company Name: _____ Contact: _____ Job Name: _____ Date: _____

Address: _____ City: _____ State: _____ Zip: _____

Phone: _____ Email: _____

Ship to Company: _____ Jobsite POC: _____

Address: _____ Jobsite Phone: _____

City: _____ State: _____ Zip: _____

Door Number	STC Rating/RF Rating	Non-STC	Opening Width	Opening Height	Rough Opening	2-pc Welded Split Frame	Slip-In Continuous	3-pc Knock Down Non-STC	Swing Handing	Wall Throat	Overall Jamb Depth	Door Material	Fire Label	Closer Opening Degree	HSS High Security Switch	Locking Device (See Below for Hardware) Mark below of best alternate	Notes

LKM10K Lock Series meets FF-L-2890C & FF-L-2740B, LKM10K Lock Series (all with US26D Finish)

- LKM10K-H-X10 (Lever/Push/Pull Handle with Key Override Housing: If Key Override is required, select (Medeco, Best/Falcon, Schlage, Sargent, Corbin Yale)
- LMK10K-P-X10 (Lever/Panic Bar with Key Override Housing: If Key Override is required, select (Medeco, Best/Falcon, Schlage, Sargent, Corbin Yale)
- LKM10KH10SA w/Standalone Access Control
- LKM10KPX10SA w/Standalone Access Control
- LKM10K-HE (Push/Pull Handle Exit Only with Deadbolt status switch) LKM10K-PE (Panic Bar Exit Only with Deadbolt status switch) Alarm Kit Optional
- Include Automatic Bolt Retraction (ABR)

- Kaba Mas CDX10 with Lever Lock Grade 1 Cylindrical Grade 1 Mortise (Specify manufacture & model number)
- SG2890 Type I, II, III, IV, V, VI with KABAX10 or SG2740
- Grade 1 Cylindrical (Specify manufacturer & model number) Grade 1 Mortise (Specify manufacturer & model number)
- Electric Strike (Specify manufacturer & model number) Grade 1 Exit Device (Specify manufacturer & model number)

Note: We also offer STC, HMD, WOOD, BULLET RESISTANT, BLAST RESISTANT GSA VAULT DOORS, STC/RF SHIELDING

1. Please review hardware list must have manufacturer and model number
 2. All frames have 1/2" returns
 3. If 4" header is needed please allow extra lead time
 4. Jamb depth = throat + 1"
 5. Cylindrical locks require a 3-3/4" backset in order to avoid interference with sound seal assembly
 6. Standard pair with astragal surface bolts at inactive leaves are recommended
 7. Standard pair with mullion both leaves active or Standard pair with astragal flush bolts at inactive leaves extra lead time
 8. STC door size 3070 (3'x 7'), rough opening required for 2-pc split frame (39"x 85-1/2")
 9. STC door size 3070 (3'x 7'), rough opening required for 1-pc slip in frame (40 1/2"x 86-1/2")
- Recommended all rough openings with steel studs should be wood blocked for extra support

Fill in door vision dimensions 100 sq. max
 (If vision lite required, please advise glass thickness, glass and glazing is by others)

A = _____
 B = _____
 X = _____
 Y = _____

